

**GRAPHIC PRODUCTS** 

## COATING UV7115 Flexo Gloss FB FCM ES

Galaxy Coating UV7115 is a radical curing UV varnish with a high reactivity and special waxes for improved slip properties designed for flexographic printing. In the fully cured print the coating shows very low odour. UV7115 is formulated for food packaging according EC 1935/2004, when migration testing is carried out by the end user. Compliant with Nestlé list 10-2018, Swiss Ordinance for Food Packaging and EuPIA recommendations. Does not contain Bisphenol A.

Application:	Recommended coating weight 2 – 4 grms/m2 (wet) Suitable for paper (coated), board, certain treated plastics and foils FCM coatings are not recommended for use on high absorbent substrates Suitable for conventional anilox and roller coater			
Use:	Use solvent and alkali resistant inks Press ready Optimal properties obtained 24hrs after printing Suitable for use in food packaging industry, sensitive packaging applications, appropriate migration tests are recommended for full suitability			
Performance key:	Gloss Cure speed Slip Rub resistance Block resistance Glueability Solvent resistance	10 5 4 5 3 5 4	1 matt – 10 h Specific films Specific condi	
	** 1 (Slow / Low) – 5 (Fast / High) **			
Typical constants:	Viscosity Specific gravity Apearance	50 secs @ 25°C 1.10 g/cm³ Brownish, hazy liquid		± 6 ± 0.05
Storage conditions:	Store away from excessive heat, out of direct sunlight and in closed packaging. Prefered conditions between 15 - 20°C			
Cleaning:	Use a proper UV-wash, UV-Wash UV4000-IQ-S			
Shelf lifetime:	In unopened, original packaging, 8 months from manufacturing date			

www.atece.com





Version: 01-2012

The information provided in this technical data sheet is to inform our customers. A succesful application depends on a variety of different factors. Therefore the advice given in this technical data sheet cannot be used as basis for claims. Our recommendation is where possible to perform tests before entering production runs.

www.atece.com

