



DATA SHEET 12000.350.11300

# Folabase Soft U

UNDERPACKING FOIL, NON ADHESIVE

Folabase Soft U offers reliable support for adaptation to cylinder circumferences and print lengths in offset printing presses and ensures optimum dot transfer.

The two-layer compound made of dimensionally stable polyester and extremely ductile polyurethane ensures an extremely high dimensional stability and consistent thickness.

Unlike paper-based underpacking sheets the Folabase Soft U has a certain smash resistance and can be used again. Additionally it is highly swell resistant to dampening solutions and cleaning agents.

For product introduction by video please click here.

Formats		
Art.Number	Nominal thickness (inch)	Nominal thickness (mm)
12001.350.99900	.014	0.35
12001.400.99900	.016	0.40
12001.450.99900	.018	0.45
12001.500.99900	.020	0.50
12001.550.99900	.022	0.55
12001.600.99900	.024	0.60
12001.700.99900	.028	0.70
12001.750.99900	.030	0.75
12001.800.99900	.031	0.80
12001.900.99900	.035	0.90
12001.950.99900	.037	0.95
12001.105.99900	.041	1.05
12001.110.99900	.043	1.10
12001.130.99900	.051	1.30
12001.145.99900	.057	1.45



#### Rolls Nominal thickness Art.Number Width (mm) Length (m) Nominal thickness (inch) (mm) 12000.350.11300 1270 50 .014 0.35 12001.400.11300 1270 50 .016 0.40 12001.450.11300 1270 .018 0.45 12001.500.11300 1270 .020 0.50 12001.550.11300 1270 .022 0.55 12001.600.11300 1270 .024 0.60 12001.700.11300 1270 .028 0.70 12001.750.11300 .030 1270 0.75 12001.800.11300 1270 .031 0.80 12001.900.11300 1270 .035 0.90 12001.950.11300 1270 .037 0.95 1270 .041 12001.105.11300 50 1.05

50

50

50

.043

.051

.057

1.10

1.30

1.45

## Technical data

12001.110.11300

12001.130.11300

12001.145.11300

#### Characteristic





• Paper jam-resistant Crease-resistant / self-healing

1270

1270

1270

• Polyester-basis/ -carrier

#### **Finish**

Soft surface

#### Compatibility

· Paperlike underpacking film

### Product liability clause

The foregoing information and any consulting provided by us in terms of application engineering shall be given to our best knowledge, but shall not be considered binding information neither with regard to any third party industrial property rights. Any such consulting shall not relieve you from your own review of our current consulting information as to their suitability for the intended procedures and applications. These shall be beyond our control, and be subject to your exclusive responsibility. The sale of our products shall be





subject to our current General Terms and Conditions.







